STATE MO EFFECTIVE 07-01-2002 JOB NO. PROJECT NO. COUNTY DATE_ CENTERL INE 24' CROSS SLOPE SHLDR TRAVELED WAY SHLDR GROUND LINE 12' 12' PROFILE GRADE (1) — (2) GROUND LINE SLOPE _:1 * SECTION ON TANGENT SLOPE _:1 ** TYPICAL SECTION RTE. XX STA. XXX.XX TO STA. XXX.XX SEE STANDARDS 203.20. 606.00 AND 609.40 FOR SHOULDER WIDENING. CENTERLINE SHLDR SHLDR TRAVELED WAY GROUND LINE PROFILE GRADE ___ S.E. SLOPE --- (3) S.E. SLOPE (3) GROUND LINE SLOPE _:1 * SLOPE _:1 ** SECTION ON SUPERELEVATED CURVE TYPICAL SECTION RTE. XX STA. XXX.XX TO STA. XXX.XX * BACKSLOPE DETERMINED BY SOIL SURVEY. ** BACKSLOPE DELEMMINED BY SUIL SURVEY.

*** THE FILL SLOPE SHALL BE 4:10 PF FLATTER WHEN THE
FILL HEIGHT IS EDUAL TO OR LESS THAN 2 FEET II.E.
THE OFFSET FROM THE TOE OF FILL 10 THE SHOULDER
POINT IS A MINIMUM OF 8 FEET). THE SLOPE MAY VARY
TO MEET THIS REDUREMENT, FOR FILL HEIGHTS GREATER
THAN 2 FEET. THIS SLOPE SHALL NOT EXCEED THE
MAXIMUM SLOPE DETERMINED BY THE SOIL SURVEY. 4' DITCH DEPTH PREFERRED IF ALTERNATE 2' ROCK BASE IS USED. SIDESLOPE WIDTH SHALL BE 16' FOR 4' DITCH DEPTH.

FUNCTION

TRAVELED WAY WIDTH 24' ROADBED WIDTH

ADT

D-64E

36

2'

4:1

< 1700

MINOR ARTERIAL

